



US009409471B2

(12) **United States Patent**
Hoppe et al.

(10) **Patent No.:** **US 9,409,471 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **VEHICLE AND METHOD FOR MOUNTING A DRIVE ASSEMBLY**

(75) Inventors: **Tobias Hoppe**, Kassel (DE); **Achim Landgrebe**, Kassel (DE)

(73) Assignee: **KRAUSS-MAFFEI WEGMANN GMBH & CO. KG**, Munich (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 16 days.

(21) Appl. No.: **14/131,662**

(22) PCT Filed: **Jul. 3, 2012**

(86) PCT No.: **PCT/DE2012/100197**

§ 371 (c)(1),
(2), (4) Date: **Feb. 14, 2014**

(87) PCT Pub. No.: **WO2013/007249**

PCT Pub. Date: **Jan. 17, 2013**

(65) **Prior Publication Data**

US 2014/0151142 A1 Jun. 5, 2014

(30) **Foreign Application Priority Data**

Jul. 8, 2011 (DE) 10 2011 051 687

(51) **Int. Cl.**
B60K 5/00 (2006.01)
F41H 7/04 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC . **B60K 5/00** (2013.01); **B62D 21/11** (2013.01);
F41H 7/048 (2013.01); **B62D 65/10** (2013.01);
Y10T 29/49229 (2015.01)

(58) **Field of Classification Search**
CPC B60K 5/00; B60K 5/08; B60K 5/12;
B60K 5/1208; B60K 5/1216; B60K 5/1233;
B60K 5/1283; B60K 6/00; B60K 6/20;

B60K 6/52; B60K 7/00; B60K 2007/0038;
B60K 2007/0092; B60G 2206/60; B62D
21/00; B62D 21/02; B62D 21/12; B62D
21/18; B62D 21/11; B62D 24/00; B62D
25/00; B62D 25/08; B62D 25/082; B62D
23/00; B62D 23/005; B62D 25/085; F41H
7/00; F41H 7/048

USPC 180/291, 311, 312, 89.1; 280/781, 785
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,115,945 A * 12/1963 Dry B60G 9/00
105/106
4,040,640 A * 8/1977 Begg 180/292

(Continued)

FOREIGN PATENT DOCUMENTS

DE 19860794 7/2000
DE 10045749 3/2001

(Continued)

OTHER PUBLICATIONS

PCT, International Search Report; International Patent Application
No. PCT/DE2012/100197 (Nov. 10, 2012).

Primary Examiner — James M Dolak

(74) *Attorney, Agent, or Firm* — Thompson Hine LLP

(57) **ABSTRACT**

A vehicle, in particular, a military vehicle, includes a self-supporting vehicle body (2) and a drive assembly (3) for driving the vehicle. The drive assembly (3) is connected to the vehicle body (2) via an assembly support (6, 7), the assembly support (6, 7) forming a part of the support structure of the vehicle body (2). In a method for mounting a drive assembly (3) in a vehicle (2) that has a self-supporting vehicle body (2), the drive assembly (3) is connected to the vehicle body (2) via an assembly support (6, 7) and the assembly support (6, 7) forms a part of the support structure of the vehicle body (2) in the mounted state.

14 Claims, 8 Drawing Sheets

